

## Weighing and Radio Technology

Weighing Equipment	Range	Remarks
Dynamometer range	2T, 6.5T, 12.5T, 25T, 55T, 120T	Wireless available
Load Cells	1 to 500 Ton	< 0.1 %
Load Pins	0.1 to 1000 Ton	Atex available
Shackle Pins	6.5 to 250 Ton	Atex available
Bellow Bending	10 to 200 Kg.	Atex available
WT-1	3.5 Ton x Rev.	Wire ø 6-15 mm
WT-2	8.5 Ton x Rev.	Wire ø14-28 mm
OL-3000	4-20 mA output	2 relay output
Mechanical overload	2T to 10 Ton	2 Switch available
Displays	14, 57, 102 mm	Linearization Digit size

Radio Equipment	Range	Remarks
TX	433.076 - 434.775 Mhz	2 - 4 - 8 - 10 - 12 Buttons.
RX	433.076 - 434.775 Mhz	3 - 15 - 16 - 24 Relays



Singapore office:

Vetec Asia Pacific Pte. Ltd.  
8 Selegie Road #03-13  
180008 Singapore  
Phone: +65 68844002  
Hp: +65 81279082  
Fax: +65 63377712

Email: [LSK@esmapservices.com.sg](mailto:LSK@esmapservices.com.sg)

Denmark Head office:

Vetec ApS  
Lucernemarken 18  
DK-5260 Odense  
Denmark  
Phone: +45 65919802  
Fax: +45 65918802  
Email: [post@vetec.dk](mailto:post@vetec.dk)  
Web: [www.vetec.dk](http://www.vetec.dk)

Customized Weighing Solutions and Radio Remote Controls for

Cranes - Marine - Conveyor belts - Gates - Wind Power - Lifts - Automation