

# Electric Dynamometer

Underhook/Inline Load Link



D2000A-XT

## Under hook / Inline load link

|                    |   |
|--------------------|---|
| Article number:    | D2000A-2T, D2000A-6,5T, D2000A-12,5T, D2000A-25T<br>D2000A-55T, D2000A-120T   |
| Application areas: | Electric weight dynamometer and calibration for weight sensors for hoisting equipment   |
| Accuracy:          | 0,2% +-1d.  |
| Input:             | Charge input niMh charger 4-10 cell   |
| Bold diameter:     | D2000A-2T; 16 mm<br>D2000A-6,5T; 25,5 mm<br>D2000A-12,5T; 35,5 mm<br>D2000A-25T; 51 mm<br>D2000A-55T; 70 mm<br>D2000A-120T; 100 mm  |
| Size (W x h):      | D2000A-2T 95 X 150 mm, Weight in kg 2,5<br>D2000A-6,5T; 95 X 220 mm, Weight in kg 4<br>D2000A-12,5T; 95 X 250 mm, Weight in kg 4,5<br>D2000A-25T; 108 X 340 mm, Weight in kg 8<br>D2000A-55T; 160 X 440 mm, Weight in kg 16<br>D2000A-120T; 200 X 500 mm, Weight in kg 37 |
| Features:          | Can communicate with external radio receiver (2000B-6V-RTX)   |
| IP classification: | IP62  |



D1004-4-RF



2000B-6V-RTX